APPLICATION:		PRODUCT NAME:
		SERVICE SINK FAUCET WITH LONG SPOUT AND VACUUM BREAKER
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
	1" 4mm] FEMALEINLETS	■ 8253
		OPTIONS OR MODIFICATIONS:
		☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
@T@		□ NIPPLES
		□ ELBOWS
1279.4		☐ VANDAL RESISTANT KIT
12"		☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
[304.8mm]		OTHER
41/8" [105.9mr	5-1/8" [130.3mm]	FEATURES:
7-3/4"-8-1/4" [196.9mm-209.6mm]	3-1/8" [80.5mm]	CONTROL VALVE * ECCENTRICS ADJUST FROM 7-3/4" TO 8-1/4" * INTERNAL SPRING LOADED CHECK VALVES * SWIVELING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * ATMOSPHERIC VACUUM BREAKER * 3/4" GARDEN HOSE THREAD OUTLET
		SYSTEM LIMITS * TEMP: 40°F MIN. TO 160°F MAX. * PRESSURE 200 PSI MAX. STATIC * 13.6 GPM AT 80 PSI
ROUGH-IN:		SHIPPING WEIGHT * 6.25 LBS
GARDENHOSE THREAD 1/2"NPT FEMALE 6-1/4" [158.8mm] 1/2"MALE (NOTINCLUDED)		
Ø7/8"[22.2mm]/ ROUGH-INHOLES		FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238
(R) ANCI/A112 10 1M		1 1 2 2 3 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1

information@fisher-mfg.com - www.fisher-mfg.com

(F)

ANSI/A112.18.1M

SPEC. FAHB-SSL-8AWZZLL REV. C